

Model: HCD-15EH

15-inch Security Surveillance TFT LCD Monitor



The HCD EH Series of high performance LCD monitors are designed specifically for the security industry to display high quality composite video or computer signals using multiple inputs.

Specifications:

LCD Panel Pixel Array	1280 x 1024 Hz
Panel Aspect Ratio	4:3
Viewing Area	304 x 228 mm
Pixel Pitch	0.297 x 0.297 mm
Brightness	250 cd/m ²
Contrast Ratio	700:1
Backlight Type	4 CCFL
Panel Lamp Life	40,000 Hours
Display Colors	16.2 Million
Response Time	8ms
Speakers	Integrated, 2 x 1.0 W
Horizontal Frequency	30kHz to 60kHz
Vertical Frequency	56 Hz to 75 Hz
Input Interfaces (Video)	1 BNC w/ Looping 1 S-Video, 1 VGA, 1 RCA
Input Interfaces (Audio)	1 (L/R) RCA
Sync Format	NTSC/PAL Autosensing
Operating Temperature	32 to 104F (0 to 40C)
Dimensions	14.17 x 15.15 x 7.08 inch
Weight	6.8 lb

- Space-Saving, Flat Panel Design
- Low-Profile-Style Desktop Stand
- Four Long Life CCFT Backlights
- NTSC & PAL Autodetect
- Looping Composite Input and S-Video Input
- VGA Input and Deinterlacing for High Quality Video
- 2-D Digital Comb & 2-D Noise Filter
- VGA PC Input w/ RCA Video Input
- Maximum Brightness of 250 cd/m² (HCD-15EH)
- Maximum Contrast Ratio of 700:1 (HCD-15EH)
- Maximum Response Time of 8ms (HCD-15EH)
- 100/240 VAC, 60/50 Hz Autoranging Power Supply
- Low Power Consumption (<50 W)



More Images



*Actual Product May Differ From Image