

Model: HCD-17MAH

17-inch Security Surveillance TFT LCD Monitor



Specifications:

LCD Panel Pixel Array	1280 x 1024 Hz
Panel Aspect Ratio	4:3
Viewing Area	338 x 270 mm
Pixel Pitch	0.264 x 0.264 mm
Brightness	300 cd/m2
Contrast Ratio	700:1
Backlight Type	4 CCFL
Panel Lamp Life	40,000 Hours
Display Colors	16.2 Million
Response Time	12ms
Speakers	Integrated, 2 x 1.0 W
Horizontal Frequency	30kHz to 60kHz
Vertical Frequency	56 Hz to 75 Hz
Input Interfaces (Video)	2 BNC w/ Looping 1 S-Video w/ Looping 1 VGA, 1 DVI
Input Interfaces (Audio)	1 (L/R) RCA
Sync Format	NTSC/PAL Autosensing
Operating Temperature	32 to 104F (0 to 40C)
Dimensions	15.03"W x 13.46"H x 3.07"D
Unit Weight	15.6 lbs

The HCD MAH Series of high performance LCD monitors are designed specifically for the security industry to display high quality composite video or computer signals using multiple inputs.

- Space-Saving, Flat Panel Design
- Picture-Frame-Style Desktop Stand
- Four Long Life CCFT Backlights
- NTSC & PAL Autodetect
- BNC Composite Inputs and S-Video Input
- VGA Input and Deinterlacing for High Quality Video
- 3-D Digital Comb Filter
- Digital DVI Input
- Maximum Brightness of 300 cd/m2 (HCD-17MAH)
- Maximum Contrast Ratio of 700:1 (HCD-17MAH)
- Maximum Response Time of 12ms (HCD-17MAH)
- 100/240 VAC, 60/50 Hz Autoranging Power Supply
- Low Power Consumption (<50 W)



More Images



*Actual Product May Differ From Image