




HTC-11 Series IR LED Vandal Dome Camera


- 18-24 IR LED, 80 ft Range.
- Vandal/Water Resistant
- Recess with 3-Axis Mount
- Auto Tracing White Balance
- 2H Mode of H.V. Aperture Correction
- Electronic Shutter up to 1/100,000
- Vari-Focal Auto Iris Lens
- 24VAC / 12VDC, Dual Voltage



HTC-11 Back Plate



Model Number	Day/ Night	LENS	Resolution	Color	Dual Voltage	Sensitivity	IR Sensitivity
HTC-11G36IR	Y	3.6mm	580 TVL	Y	24VAC/ 12VDC	0 Lux	850~940nm
HTC-11G28DID	Y	2.8~10mm	580 TVL	Y	24VAC/ 12VDC	0 Lux	850~940nm
HTC-11C36IR	Y	3.6mm	400 TVL	Y	24VAC/ 12VDC	0 Lux	850~940nm
HTC-11C28DID	Y	2.8~10mm	400 TVL	Y	24VAC/ 12VDC	0 Lux </tr	



INDICATION PARTS

1. 3-Axis Dome camera
2. 1/32" x1" screws
3. Plastic dome cover
4. BNC cable
5. Power cable

SPECIFICATIONS

ITEM NO	HTC-11G36IR	HTC-11G28DID	HTC-11C36IR	HTC-11CC28DID
PICK UP DEVICE	1/3" Sony CCD			
PIXEL (TOTAL)	811H x 508V			
PIXEL (EFFECTIVE)	768H x 494V			
OPTICS	3.6mm Fixed	2.8~10mm Fixed	3.6mm Fixed	2.8~10mm
IR LED	24	18	24	18
IR RANGE	80 FT	80 FT	80 FT	80 ft
H. SYNC FREQUENCY	NTSC 15.734 KHz / PAL 15.625 KHz			
V. SYNC FREQUENCY	NTSC 59.95 Hz / PAL 50 Hz			
SCANNING SYSTEM	2:1 INTERLACE			
SENSITIVITY	0.08 LUX			
SYNCHRONIZATION	INTERNAL			
S/N RATIO	MORE THAN 48 dB (AGC OFF)			
BACK LIGHT COMPENSATION	ON / OFF SWITCH			
ELECTRONIC SHUTTER	ON / OFF SWITCH; RANGE 1/50 (1/60) UP TO 1/100,000			
GAIN CONTROL	ON / OFF SWITCH			
GAMMA	0.45			
VIDEO OUTPUT	1 Vpp, 75 Ohms			
POWER SUPPLY	DC12V / AC 24V, DUAL POWER			
POWER CONSUMPTION	DC 200 mA, AC 2.4w			
WEIGHT	700gr			
DIMENSIONS	Ø132* 106mm			
STORAGE TEMPERATURE	-30 TO +60C			
OPERATION TEMPERATURE	-10 TO +45C			