





HTC-15 Series Indoor Dome IR Camera

- 18-24 IR LED, from 40 to 80 ft Range
- High Resolution 580 TVL
- Recess with 3-Axis Mount
- Auto Tracing White Balance
- 2H Mode of H.V. Aperture Correction
- Electronic Shutter up to 1/100,000
- Vari-Focal Auto Iris Lens
- 24VAC / 12VDC, Dual Voltage



BUILDING A NEW SECURE ERA

Model Number	IR LED/RANGE	LENS	Resolution	Color	Dual Voltage	Sensitivity	IR Sensitivity
HTC-15G28DID	18, 80 ft	2.8-10mm	580 TVL	Y	24VAC/ 12VDC	0.08 Lux	850-940nm
HTC-15C28DID	18, 80 ft	2.8-10mm	580 TVL	Y	24VAC/ 12VDC	0.08 Lux	850-940nm
HTC-15G36	24, 80 ft	3.6mm Fixed	400 TVL	Y	24VAC/ 12VDC	0.08 Lux	850-940nm
HTC-15C36	24, 80 ft	3.6mm Fixed	400 TVL	Y	24VAC/ 12VDC	0.08 Lux	850-940nm



SPECIFICATIONS

ITEM NO	HTC-15G28DID	HTC-15C28DID	HTC-15G36	HTC-15C36
PICK UP DEVICE	1/3" Sony CCD			
PIXEL (TOTAL)	811H x 508V			
PIXEL (EFFECTIVE)	768H x 494V			
OPTICS	2.8-10mm	2.8-10mm	3.6mm Fixed	3.6mm Fixed
RESOLUTION	580 TVL	400 TVL	580 TVL	400 TVL
IR LED	18 LED	18 LED	24 LED	24 LED
IR RANGE	80 FT	80 FT	80 FT	80 FT
H. SYNC FREQUENCY	NTSC 15.734 KHz / PAL 15.625 KHz			
V. SYNC FREQUENCY	NTSC 59.95 Hz / PAL 50 Hz			
SCANNING SYSTEM	2:1 INTERLACE			
SENSITIVITY	0.08 LUX			
SYNCHRONIZATION	INTERNAL			
S/N RATIO	MORE THAN 48 dB (AGC OFF)			
BACK LIGHT COMPENSATION	ON / OFF SWITCH			
ELECTRONIC SHUTTER	ON / OFF SWITCH; RANGE 1/50 (1/60) UP TO 1/100,000			
GAIN CONTROL	ON / OFF SWITCH			
GAMMA	0.45			
VIDEO OUTPUT	1 Vpp, 75 Ohms			
POWER SUPPLY	DC12V / AC 24V, DUAL POWER			
POWER CONSUMPTION	DC 200 mA, AC 2.4w			
WEIGHT	700gr			
DIMENSIONS	Ø5.5" * H4.5inch			
STORAGE TEMPERATURE	-30 TO +60C			
OPERATION TEMPERATURE	-10 TO +45C			