

MINIATURE BULLET CAMERA

HTC-230 / HTC-190



- * Full digital process of BLC
- * Auto White Balance
- * 2H mode of H.V. aperture correction
- * Digital process of color matrix
- * Electronic Shutter up to 1/100,000

SPECIFICATIONS

ITEM NO	MONOCHROME	COLOR
	HTC-191/ HTC-190	HTC-231/ HTC-230
Pick Up Device	1/4" CCD Sensor	1/3" CCD Sensor
Image Size H * V mm	3.61 * 2.72	3.61 * 2.72
Picture Elements	NTSC: 512H*492V PAL: 512H*582V	EIA: 512H * 492V CCIR:512H * 582 V
Horizontal Resolution	More Than 420 TV Lines	More Than 400 TV Lines
Horizontal Frequency	NTSC: 15.734 KHz PAL: 15.625 KHz	EIA: 15.734 KHz CCIR: 15.625 KHz
Vertical Frequency	NTSC: 60Hz PAL: 50Hz	EIA: 60Hz CCIR: 50Hz
Scanning System	2 : 1 Interlace	
Sensitivity	1.0 Lux F=1.4	0.1 Lux F=1.4
Sync. System	Internal	
S/N Ratio	More Than 46dB (AGC Off)	
Electronic Shutter	Up To 1/100,000 sec. (Linear)	
White Balance	Auto White Balance	
Gamma Correction	0.45	
Back Light Compensation	Automatic	
Video Output	1Vpp, 75 Ohms Composite	
Mount Lens	3.6 mm	
Auto Gain Control	Automatic	
Power Supply	12V DC (+/- 10 %)	
Power Consumption	115 mA for 12V DC	220 mA for 12V DC
Weight	150g	
Storage Temperature	-30°C ~ +60°C	
Operating Temperature	-10°C ~ +45°C	

Specifications are Subject to Change without Notice.



HUNT ELECTRONIC USA, INC.

Hunt Electronic is registered trademark of Hunt Electronic USA Incorporated, 2002 All rights reserved.

<http://www.huntcctv.com>