

HIDDEN TYPE CAMERA

HTC-3005S / HTC-3006S

- * Full digital process of BLC
- * Auto White Balance
- * 2H mode of H.V. aperture correction
- * Digital process of color matrix
- * Electronic Shutter up to 1/100,000



3006 Series



3005 Series

SPECIFICATIONS

ITEMS	MONOCHROME	COLOR
	HTB-3005S/ HTB-3006S	HTC-3005S/ HTC-3006S
Pick Up Device	1/3" CCD Sensor	
Image Size H * V mm	3.61 * 2.72	
Picture Elements	EIA: 512H * 492V CCIR: 512H * 582 V	NTSC: 512H * 492V PAL: 512H * 582 V
Horizontal Resolution	More Than 420 TV Lines	More Than 400 TV Lines
Horizontal Frequency	EIA: 15.734 KHz CCIR: 15.625 KHz	NTSC: 15.734 KHz PAL: 15.625 KHz
Vertical Frequency	EIA: 60Hz CCIR: 50Hz	NTSC: 60Hz PAL: 50Hz
Scanning System	2 : 1 Interlace	
Sensitivity	0.01 Lux F=1.4	1.0 Lux F=1.4
Sync. System	Internal	
S/n Ratio	More Than 46dB (AGC Off)	
Electronic Shutter	Up To 1/100,000 sec. (Linear)	Up To 1/100,000 sec. (Linear)
White Balance	None	Auto White balance
Gamma Correction	0.45	
Flickless Function	Yes (Optional)	
Back Light Compensation	Automatic	
Video Output	1 Vpp, 75 Ohms Composite	
Lens	3.7 mm pinhole, 5.5 mm pinhole	
Auto Gain Control	Automatic	
Power Supply	12V DC (+/-10%)	
Power Consumption	115 mA for 12V DC	220 mA for 12V DC
Storage Temperature	-30°C to + 60°C	
Operating Temperature	-10°C to + 45°C	

Specifications are Subject to Change without Notice.



HUNT ELECTRONIC USA, INC.

Hunt Electronic is registered trademark of Hunt Electronic USA Incorporated, 2002 All rights reserved.

<http://www.huntcctv.com>